

228 Commander P.I.G.

CAPACITY

MAX. WEIGHT CAPACITY	2200			
PERSONS (QUANTITY) (SEATING FOR 8)	8			
PERSONS (LBS.)	1200			
MAX H.P.	250	HP	186	KW

SPECIFICATION

L.O.A.	268	IN	22'-4"/6.8	FT/M
L.W.L.	216	IN	18'-0"/ 5.5	FT/M
BEAM	102	IN	8'-6"/2.59	FT/M
DEAD RISE	18	DEG		
DEAD RISE BOW ENTRY POINT	34	DEG		
TRANSOM ANGLE	15	DEG		
STATIC FLOAT ANGLE (KEEL TO BOW)	0	DEG		
TRANSOM HEIGHT(Center line)	25	IN	0.64	METER
TRANSOM WIDTH	94	IN	2.39	METER
COCKPIT DEPTH AFT	24	IN	0.61	METER
COCKPIT DEPTH BOW	30	IN	0.76	METER
FREEBOARD AFT	29	IN	0.74	METER
FREEBOARD BOW (BOW TO WATER LINE TROLLING MOTOR)	40	IN	1.02	METER
DRAFT	14	IN	0.36	METER
DEPTH	56	IN	1.42	METER
CENTER OF GRAVITY FROM KEEL/TRANSOM	92	IN	2.34	METER
HEIGHT, KEEL TO CONSOLE RAIL	92	IN	2.34	METER
HEIGHT, KEEL TO TOP (LIGHT FOLDED)	115	IN	2.92	METER
BRIDGE CLEARANCE TO CONSOLE RAILS	78	IN	1.98	METER
BRIDGE CLEARANCE W/TOP	99	IN	2.51	METER
CABIN HEIGHT	56	IN	1.42	METER
DRY WEIGHT BOAT: w/ options but no Gear, Batteries, Fluids, or Motor(s)	3248.0	LBS.	1473	KG
WEIGHT BOAT (Options and Motor(s) no Fluids)	4119	LBS.	1868	KG
MAX. WEIGHT BOAT: w/batteries, Fluids, gear, largest Motor(s)	4680	LBS.	2123	KG
BATTERY QUANTITY	2 STANDARD	EA	1-H-ENG, 1 BACKUP	
PANEL SIZE FOR ELECTRONICS	13.5 W x 12 H (SINGLE MACHINE ONLY)			

TUB CAPACITY

ROPE LOCKER	13.6	CF	27"L x 58"W x 30"D	
TUB BOW PORT	40	QT	41"L x 17"W x 13"D	
TUB BOW STARBOARD	40	QT	41"L x 17"W x 13"D	
TUB BOW FLOOR (bucket)	40	QT	15"L,14"W, 14"D	
TUB FISHBOX REAR SEAT	138	QT	12"L,56"W, 13"D	
TUB COOLER/ DAY ANCHOR -AFT OF GATE	56	QT	16"L,15"W, 15"D	
TUB BAITWELL AFT	30	GAL	19"L x 19"W x 23"D	
TUB BAITWELL LEAN POST POD (opt)	20	GAL	12"L x 26"W x 17"D	
COOLER SIZE (REMOVABLE)	65	QT	ARTIC	
FUEL TANK	90	GAL	341	LITER
FUEL SENDER	15	INCH	NA	NA
FRESH WATER	12	GAL	45	LITER
HOLDING TANK	12	GAL	45	LITER