

248 Commander P.I.G.

CAPACITY

MAX. WEIGHT CAPACITY	2500			
PERSONS (QUANTITY) (SEATING FOR 10)	10			
PERSONS (LBS.)	1500			
MAX H.P.	300	HP	224	KW

SPECIFICATION

L.O.A.	292	IN	24'-4"/7.42	FT/M
L.W.L.	241	IN	20'-1"/ 6.12	FT/M
BEAM	102	IN	8'-6"/2.59	FT/M
DEAD RISE	18	DEG		
DEAD RISE BOW ENTRY POINT	34	DEG		
TRANSOM ANGLE	15	DEG		
STATIC FLOAT ANGLE (KEEL TO BOW)	0	DEG		
TRANSOM HEIGHT(Center line)	25	IN	0.64	METER
TRANSOM WIDTH	94	IN	2.39	METER
COCKPIT DEPTH AFT	24	IN	0.61	METER
COCKPIT DEPTH BOW	30	IN	0.76	METER
FREEBOARD AFT	29	IN	0.74	METER
FREEBOARD BOW (BOW TO WATER LINE TROLLING MOTOR)	40	IN	1.02	METER
DRAFT	14	IN	0.36	METER
DEPTH	56	IN	1.42	METER
CENTER OF GRAVITY FROM KEEL/TRANSOM	101	IN	2.57	METER
HEIGHT, KEEL TO CONSOLE RAIL	92	IN	2.34	METER
HEIGHT, KEEL TO TOP (LIGHT FOLDED)	115	IN	2.92	METER
BRIDGE CLEARANCE TO CONSOLE RAILS	78	IN	1.98	METER
BRIDGE CLEARANCE W/TOP	99	IN	2.51	METER
CABIN HEIGHT	56	IN	1.42	METER
DRY WEIGHT BOAT: w/ options but no Gear, Batteries, Fluids, or Motor(s)	3793	LBS.	1720	KG
WEIGHT BOAT (Options and Motor(s) no Fluids)	4794	LBS.	2175	KG
MAX. WEIGHT BOAT: w/batteries, Fluids, gear, largest Motor(s)	5905	LBS.	2678	KG
BATTERY QUANTITY	2 STANDARD	EA	1-H-ENG, 1 BACKUP	
PANEL SIZE FOR ELECTRONICS	33 W x 10 H (TWO 10" GARMIN)			

TUB CAPACITY

ROPE LOCKER	13.6	CF	27"L x 58"W x 30"D	
TUB BOW PORT	131	QT	36"L x 15"W x 13"D	
TUB BOW STARBOARD	131	QT	36"L x 15"W x 13"D	
TUB BOW FLOOR (bucket)	40	QT	15"L,14"W, 14"D	
TUB FISHBOX REAR SEAT	138	QT	12"L,56"W, 13"D	
TUB COOLER/ DAY ANCHOR -AFT OF GATE	56	QT	16"L,15"W, 15"D	
TUB BAITWELL AFT	30	GAL	19"L x 19"W x 23"D	
TUB BAITWELL LEAN POST POD (opt)	20	GAL	12"L x 26"W x 17"D	
COOLER SIZE (REMOVABLE)	65	QT	ARTIC	

TANK CAPACITY

FUEL TANK	111	GAL	420	LITER
FUEL SENDER	14-1/2"	INCH	NA	NA
FRESH WATER	12	GAL	45	LITER
HOLDING TANK	12	GAL	45	LITER