

268 Traveler P.I.G.

CAPACITY

MAX. WEIGHT CAPACITY	YACHT CERTIFICATION			
PERSONS (QUANTITY) (SEATING FOR 12)	YACHT CERTIFICATION			
PERSONS (LBS.)	YACHT CERTIFICATION			
MAX H.P.	400	HP	298	KW

SPECIFICATION

L.O.A.	312	IN	26'-0"/ 7.9M	FT/M
L.W.L.	248	IN	20'-6"/ 6.3	FT/M
BEAM	111	IN	9'-3"/ 2.8M	FT/M
DEAD RISE	20	DEG		
DEAD RISE BOW ENTRY POINT	38	DEG		
TRANSOM ANGLE	15	DEG		
STATIC FLOAT ANGLE (KEEL TO BOW)	0	DEG		
TRANSOM HEIGHT(Center line)	30 (25 @ engine)	IN	0.76	METER
TRANSOM WIDTH	103	IN	2.62	METER
COCKPIT DEPTH AFT	27	IN	0.69	METER
COCKPIT DEPTH BOW	34	IN	0.86	METER
FREEBOARD AFT	35	IN	0.89	METER
FREEBOARD BOW (BOW TO WATER LINE TROLLING MOTOR)	49	IN	1.24	METER
DRAFT	16	IN	0.41	METER
DEPTH	62	IN	1.57	METER
CENTER OF GRAVITY FROM KEEL/TRANSOM	108	IN	2.74	METER
WATERLINE BEAM	95.625	IN	2.43	METER
WATERLINE LENGTH	244.375	IN	6.21	METER
HEIGHT, KEEL TO TOP (LIGHT FOLDED)	117	IN	2.97	METER
BRIDGE CLEARANCE W/TOP (WITH OUTRIGGERS, TALLEST OPTION)	102	IN	2.59	METER
CABIN HEIGHT (HEAD)	67	IN	1.70	METER
DRY WEIGHT BOAT: w/ options but no Gear, Batteries, Fluids, or Motor(s)	5662	LBS.	2568	KG
WEIGHT BOAT (Options and Motor(s) no Fluids)	6782	LBS.	3076	KG
MAX. WEIGHT BOAT (Options ,Fluids, Gear, largest H.P.)	8725	LBS.	3958	KG
BATTERY QUANTITY- TWIN ENGINE	3	EA	1-LE/H,1-RE,1-BKP	
BATTERY QUANTITY- STOVE OPTION	1	EA	1 GROUP 31	
PANEL SIZE FOR ELECTRONICS	21.25 W x 8.25 H (single or dual 10" Garmin)			

TUB CAPACITY

ROPE LOCKER	12	CF	32"L, 60"W,28"D	
TUB BOW PORT- combines with STBD	155	QT	38"L, 13"W, 13"D	
TUB BOW STARBOARD- Combines with Port	155	QT	38"L, 13"W, 13"D	
TUB SKI LOCKER	15	CF	26"L, 35"W, 17"D	
TUB FISH AFT PORT	117	QT	60"L, 14"W, 11"D	
TUB FISH AFT STBD	117	QT	60"L, 14"W, 11"D	
TUB BAITWELL PORT	75	GAL	20"L, 18"W, 24"D	
TUB COOLER/ DAY ANCHOR -AFT OF GATE	56	QT	16"L,15"W, 15"D	
COOLER SIZE (REMOVABLE)	65	QT	ARTC	

TANK CAPACITY

FUEL TANK	127	GAL	481	LITER
FUEL SENDER	17	INCH	NA	NA
FRESH WATER	12	GAL	64	LITER
HOLDING TANK	6	GAL	23	LITER