

Boat Manufactured By:

## SEA FOX

**BOAT WORKS**  
 2550 Highway 52 • Moncks Corner, SC  
 (843) 761-6090  
[www.seafoxboats.com](http://www.seafoxboats.com)

### SEA FOX 368 COMMANDER

Length	36' 0"
Beam	11' 0"
Dry Weight (Boat Mfr. Pub)	11,713 lbs
Maximum HP	1,200 hp
Fuel Capacity	377 gal
Weight as Tested	15,270 lbs

### LF350USA2 / F350ESA2 / F350USA2

Horsepower	350 hp
Induction	EFI/VCT/DOHC
Displacement	4.3L
Weight (Estimated)	642 - 653 - 642 lbs
Gear Ratio	1.75:1

### ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Ventilation Plate Height	3/4" Above Boat Bottom

### PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15 x 21
Yamaha Part #	6CF-45972-20-00 / 6CE-45972-20-00 / 6CE-45972-20-00
Propeller Material	Stainless Steel

### TEST CONDITIONS

Number of People	3
Air / Water Temperature (Fahrenheit)	60° F / 58° F
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

### COMMENTS

Test weight includes 100 gallons of fuel, 7 batteries, safety and test equipment.

YPB#: PB\_SFX\_368 Commander\_TR\_LF350USA2\_3-21-2024\_OCC



**Engine:** Yamaha LF350USA2 / F350ESA2 / F350USA2

**Boat:** Sea Fox 368 Commander

**Configuration:** Triple

**Test Date:** 21-Mar-2024



### PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.7	3.6	1.31
1500	8.1	6.7	1.31
2000	9.9	10.7	0.92
2500	16.1	16.9	0.95
3000	27.3	22.5	1.21
<b>3500</b>	<b>35.1</b>	<b>28.7</b>	<b>1.22</b>
4000	39.8	35.7	1.11
4500	46.0	45.2	1.02
5000	50.5	58.1	0.87
5500	55.6	78.3	0.71
<b>6000</b>	<b>60.1</b>	<b>92.1</b>	<b>0.65</b>
<b>Time to Plane: 5.50 seconds</b>			
<b>0-30 MPH: 5.80 seconds</b>			

### NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in

this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.